



**DunRite
Playgrounds**

(888) 882-1929

www.dunriteplaygrounds.com
sales@dunriteplaygrounds.com

360 Tube Slide PRODUCT SPECIFICATIONS

HARDWARE

- Conforms to ANSI/ASCE-8-90
- Tamper resistant
- Special tool required for install

FITTINGS

- Aluminum alloy (GM70B) manufactured and tested in accordance with the following ASTM Standards: B179-68, B108-68, E10-66, E8-66
- Powder coat finish
- Predrilled

SEALING GASKET

- Neoprene rubber
- 60 +/- 5 durometer hardness
- Double sided adhesive

SLIDE FOOT

- 3.5" O.D. support post
- 13 gauge galvanized steel support post
- 50,000 psi yield strength (ASTM E-8)
- 55,000 psi tensile strength (ASTM E-8)
- 12 gauge galvanized steel plate
- Triple Flo-Coated corrosion protection (interior/exterior)
- Interior and exterior corrosion resistance (ASTM B-117)
- Manufactured per ASTM 500
- Powder coat finish

SLIDE SUPPORT

- 1.9" O.D. support post
- 13 gauge galvanized steel
- 50,000 psi yield strength (ASTM E-8)
- 55,000 psi tensile strength (ASTM E-8)
- Triple Flo-Coated corrosion protection (interior/exterior)
- Interior and exterior corrosion resistance (ASTM B-117)
- Manufactured per ASTM 500
- Powder coat finish

CHUTE SLIDE

- 1st quality linear low density Polyethylene (ExxonMobil LL8450)
- Rotational molded
- 3/8" Wall thickness

- 2,550 psi tensile strength (ASTM D638)
- UV stabilized
- Anti-static inhibitors

PRETREATMENT WASH PRIMER

- 4860-420 primer / 1000-44 activator
- Polyvinyl-butylal resin based primer
- Used on all milled steel and all weld joints
- Designed to give adhesion to a wide variety of metal substrates
- Provides added metal protection against rust
- Imparts extra durability to topcoat (powder coat)
- When reduced properly, it meets the definition of a "pretreatment" primer found in many air quality regulations

BARRIER

- 3/4" high density Polyethylene sheeting
- Tested in accordance with ASTM D1928 Procedure C
- Textured finish
- 4,400 psi tensile strength (ASTM D638)
- UV stabilized

POWDER COAT FINISH

- TGIC polyester
- Electrostatic application
- Baked-on @ 400 degrees
- 5-7 mills thick
- Lead free
- High gloss
- No peel / No flake finish
- Resistant to salt spray (ASTM B117)
- Resistant to humidity (ASTM D2247)
- Direct/Indirect impact 120 in. pounds (ASTM D2794)
- Good to excellent resistance to most solvents, oils, acids and alkalies