



## Hex Roof Product Specification

### **HARDWARE**

- Tamper resistant
- Special tool required for install

### **POWDER COAT FINISH**

- TGIC polyester
- Electrostatic application
- Baked-on @ 400 degrees
- 5-7 mills thick
- Lead free
- High gloss
- No peel / No flake finish
- Resistant to salt spray (ASTM B117)
- Resistant to humidity (ASTM D2247)
- Direct/Indirect impact 120 in. pounds (ASTM D2794)
- Good to excellent resistance to most solvents, oils, Acids and alkalies

### **ROOF BRACKET**

- Aluminum alloy (ANSI AA 319.0 F)
- 27 ksi Tensile strength (ultimate)
- 18 ksi Tensile strength (yield)
- 19 ksi Compressive strength (yield)

### **ROOF**

- 1st quality linear low density Polyethylene (ExxonMobil LL8450)
- Rotational molded
- 3/8" wall thickness
- 2,550 psi tensile strength (ASTM D638)
- UV stabilized
- Anti-static inhibitors

**DunRite  
Playgrounds**

(888) 882-1929

[www.dunriteplaygrounds.com](http://www.dunriteplaygrounds.com)  
[sales@dunriteplaygrounds.com](mailto:sales@dunriteplaygrounds.com)