



## Plastic Landscape Timbers and ADA Landscape Ramp PRODUCT SPECIFICATIONS

### LANDSCAPE TIMBERS - BLACK

High density polyethylene copolymer resin – DMDA-6147 Natural 7  
Blow molded  
High moldability, toughness and stress-crack resistance  
Uniform wall thickness  
5,000 psi tensile strength (ASTM D638)  
3,600 psi yield strength (ASTM D 638)  
UV Stabilized

### LANDSCAPE STAKES

$\frac{3}{4}$ "x30" dome spike bolt  
Stakes are A36 mild steel; hot dipped galvanized  
Manufactured per ASTM A153C HDG

### ADA LANDSCAPE RAMP

1<sup>st</sup> quality linear low density polyethylene (LDPE)  
Rotational molded with mold-in graphics (where applicable)  
3/8" wall thickness  
2,550 psi tensile strength (ASTM D638)  
Melt index per ASTM D1238  
Density per ASTM D4883  
Peak crystallization temperature per ASTM D3418  
Flexural modulus per ASTM D790 Procedure B  
Deflection temperature under load per ASTM D648  
Environmental stress crack resistance, F50 per ASTM D1693 Condition A  
UV stabilized / UV 8 Rating (tested per ASTM G155 cycle 1 guidelines)  
Anti-static inhibitors

**DunRite  
Playgrounds**

(888) 882-1929

[www.dunriteplaygrounds.com](http://www.dunriteplaygrounds.com)  
[sales@dunriteplaygrounds.com](mailto:sales@dunriteplaygrounds.com)